Product data sheet
Characteristics

VW3A1111
graphic display terminal, Altivar, 240 x 160pixels, IP65



Main

Range of product	Altivar
Range compatibility	Altivar Process ATV900 Altivar Process ATV600 Altivar Machine ATV340
Accessory / separate part category	Display and signalling accessories
Accessory / separate part type	Display terminal
Accessory / separate part destination	Variable speed drive
Product specific application	To control, adjust and configure the drive To save and download configurations To display the current values
IP degree of protection	IP65

Complementary

User language	Spanish Romanian Turkish Polish Swedish Estonian Bulgarian English Russian Greek Danish Hungarian Chinese Norwegian Lituanien French Brazilian German Korean Portuguese Finnish Czech Slovak Taiwanese Dutch Italian Ukrainian
Realtime clock	Built-in
Battery size	CR2032
Battery life	10 Year(S)
Display type	Backlit LCD screen white and red
Messages display capacity	8 lines

Pixel resolution	240 x 160
Net weight	0.2 Kg

Environment

Ambient air temperature for operation	-15…60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.800 Cm
Package 1 Width	14.000 Cm
Package 1 Length	18.800 Cm
Package 1 Weight	284.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	6.500 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	80
Package 3 Height	45.000 Cm
Package 3 Width	60.000 Cm
Package 3 Length	80.000 Cm
Package 3 Weight	32.776 Kg

Offer Sustainability

Recyclability potential, in %	7
Total lifecycle Carbon footprint	104 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	34.087
Carbon footprint of the manufacturing phase [A1 to A3]	34 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.033159
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0042487
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	69.552
Carbon footprint of the use phase [B2, B3, B4, B6]	70 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.1298
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	104
Packaging made with recycled cardboard	No
Packaging without single use plastic	Yes
SCIP Number	Cd0eb1b0-0b52-4d45-90f6-4bd8d825785f
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
End of life manual availability	End Of Life Information
Removable battery	Yes
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised