Product data sheet
Characteristics

TMC2SL1
communication cartridge module, Modicon M221, 1 serial line extension



Main

Range of product	Modicon M221
Product or component type	Serial line cartridge
Product compatibility	Modicon M221C

Complementary

Integrated connection type	Non isolated serial link - screw terminal block for RS232 Non isolated serial link - screw terminal block for RS485
Transmission rate	1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 15 m for RS485 1.2...115.2 kbit/s (115.2 kbit/s by default) for bus length of 3 m for RS232
Communication port protocol	Non isolated serial link: Modbus master/slave - RTU/ASCII or SoMachine-Network
Insulation	Non-insulated between lines and internal logic
Height	41 Mm
Depth	15 Mm
Width	35 Mm
Net weight	0.015 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.000 Cm
Package 1 Width	5.000 Cm
Package 1 Length	7.000 Cm
Package 1 Weight	40.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	75
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	3.170 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	2400
Package 3 Height	105.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	111.000 Kg

Offer Sustainability

Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised