Product data sheet
Characteristics

VW3A3204
additional output module, Altivar, relay output, 24 to 30V DC, 1 screw terminal



Main

Product or component type	Additional output module
Range compatibility	Altivar Machine ATV340 Altivar ATV610 Altivar Process ATV900 Altivar Process ATV600
Input/output type	3 relay output
Discrete output number	3
Discrete output type	(R4, R5, R6) relay normally open, sampling time: 1 ms

Complementary

Electrical durability	100000 Cycles
Minimum switching current	5 MA at 24 V DC
Maximum switching current	2 A at 250 V AC on inductive load, cos phi = 0.4 and L/R = 5 ms 2 A at 30 V DC on inductive load, cos phi = 0.4 and L/R = 5 ms 5 A at 250 V AC on resistive load, cos phi = 1 and L/R = 5 ms 5 A at 30 V DC on resistive load, cos phi = 1 and L/R = 5 ms
Electrical connection	Screw terminal block, 1.5 mm² / 16 AWG, 0.5 N.m
Net weight	0.4 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 Cm
Package 1 Width	13.0 Cm
Package 1 Length	19.0 Cm
Package 1 Weight	152.0 G
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	30 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	3.114 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	2a2f2e41-9976-44a1-aaef-cecaebe1de88
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
End of life manual availability	No need of specific recycling operations
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised