Product data sheet
Characteristics

VW3A4421
EMC input filter, Altivar, Lexium, 17.6A, 1 phase, 200...240V



Main

Range of product	Altivar Lexium
Product or component type	EMC input filter
Range compatibility	Lexium 32 Altivar Machine ATV320 Lexium 28 Altivar 32
Product compatibility	LXM28A ATV32, 200...240 V, 1.1...1.5 kW LXM32, single-phase, line current 8.4...12.9 A Variable speed drive ATV320...B at 1.1 kW, 200...240 V, single phase Variable speed drive ATV320...B at 1.5 kW, 200...240 V, single phase
Product specific application	Radio interference input filter
Mounting location	At variable speed drive side
Network number of phases	Single phase

Complementary

Maximum cable distance between devices	20 M conforming to IEC 61800-3 category C1 50 M conforming to IEC 61800-3 category C2
[In] rated current	17.6 A
Thermal losses	6.9 W
Network rated voltage	200…240 V
Tolerance	- 15...10 %
Net weight	0.775 Kg
Emc filter compatibility	Type 021

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.000 Cm
Package 1 Width	18.000 Cm
Package 1 Length	23.300 Cm
Package 1 Weight	634.000 G
Unit Type of Package 2	S06
Number of Units in Package 2	84
Package 2 Height	75.000 Cm
Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	66.256 Kg

Offer Sustainability

Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised