Product data sheet
Characteristics

VW3A4423
EMC input filter, Altivar, Lexium, 25A, 3 phases, 380 to 480V



Main

Range of product	Altivar Lexium
Product or component type	EMC input filter
Range compatibility	Lexium 32 Lexium 52 Lexium 28 Altivar Machine ATV340
Product compatibility	LXM28A LXM32, three-phase, line current 14.6...18.1 A Variable speed drive ATV340 at 2.2 kW, 380...480 V Variable speed drive ATV340 at 3 kW, 380...480 V Variable speed drive ATV340 at 4 kW, 380...480 V Variable speed drive ATV340 at 5.5 kW, 380...480 V Variable speed drive ATV340 at 7.5 kW, 380...480 V
Product specific application	Radio interference input filter
Mounting location	At variable speed drive side
Network number of phases	Three phase

Complementary

Maximum cable distance between devices	20 M conforming to IEC 61800-3 category C1 50 M conforming to IEC 61800-3 category C2 100 M conforming to IEC 61800-3 category C3
[In] rated current	25 A
Thermal losses	15.8 W
Network rated voltage	380…500 V
Tolerance	- 15...10 %
Net weight	1.35 Kg
Emc filter compatibility	Type 023

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.200 Cm
Package 1 Width	22.400 Cm
Package 1 Length	29.600 Cm
Package 1 Weight	1.532 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	44
Package 2 Height	75.000 Cm
Package 2 Width	60.000 Cm

Package 2 Length	80.000 Cm
Package 2 Weight	65.736 Kg

Offer Sustainability

Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised