Product data sheet
Characteristics

VW3A4712
additionnal EMC filter - 70 A - IP20



Main

Range of product	Altivar
Product or component type	EMC input filter
Range compatibility	Altivar Machine ATV340
Product compatibility	Variable speed drive ATV340 motor: 18.5 kW, 380...480 V[RETURN]Variable speed drive ATV
Product specific application	Radio interference input filter
Mounting location	At variable speed drive side
[In] rated current	70 A
Thermal losses	10 W
Network number of phases	Three phase

Complementary

Electrical connection	Terminal 35 mm² 3 AWG
Maximum motor cable length	100 M shielded motor cable 4 kHz conforming to IEC 61800-3 category C3, 380...480 V 50 M shielded motor cable 4 kHz conforming to IEC 61800-3 category C2, 380...480 V
Earth leakage current	3.98 MA at 400 V 50 Hz TN
Network rated voltage	380…480 V
Tolerance	10 %
Mechanical robustness	Shocks class 3M4 conforming to IEC 60721-3-3 Vibrations class 3M4 conforming to IEC 60721-3-3
Width	100 Mm
Height	330 Mm
Depth	180 Mm
Net weight	6.1 Kg

Environment

IP degree of protection	IP20mounting side by side
Relative humidity	5…95 % without condensation conforming to IEC 61800-5-1
Ambient air temperature for operation	-10…50 °C (without current derating) 50…60 °C (with current derating 1.5 % per °C)
Ambient air temperature for storage	-40…70 °C
Operating altitude	0...1000 m without current derating 1000...4000 m with current derating 1 % per 100 m
Standards	IEC 61800-3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.800 Cm
Package 1 Width	37.500 Cm
Package 1 Length	53.000 Cm
Package 1 Weight	7.416 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	75.000 Cm
Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	38.164 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised