Product data sheet
Characteristics

VW3A5305
output dv dt filter, Altivar, for variable speed drive, 15 to 45kW, 95A, IP20



Main

Product or component type	Dv/Dt filter
Range compatibility	Altivar Process ATV600 Altivar Process ATV900 Altivar Machine ATV340 Altivar ATV610
Product specific application	Output filter
[In] rated current	95 A
Product compatibility	ATV630 variable speed drive wall mount - 15 kW, 200...240 V ATV630 variable speed drive wall mount - 18.5 kW, 200...240 V ATV630 variable speed drive wall mount - 22 kW, 200...240 V ATV630 variable speed drive wall mount - 30 kW, 380...480 V ATV630 variable speed drive wall mount - 37 kW, 380...480 V ATV630 variable speed drive wall mount - 45 kW, 380...480 V ATV650 variable speed drive wall mount - 30 kW, 380...480 V ATV650 variable speed drive wall mount - 37 kW, 380...480 V ATV650 variable speed drive wall mount - 45 kW, 380...480 V ATV610 variable speed drive - 30 kW, 380...415 V ATV610 variable speed drive - 37 kW, 380...415 V ATV610 variable speed drive - 45 kW, 380...415 V ATV930 variable speed drive wall mount - 15 kW, 200...240 V ATV930 variable speed drive wall mount - 18.5 kW, 200...240 V ATV930 variable speed drive wall mount - 22 kW, 200...240 V ATV930 variable speed drive wall mount - 30 kW, 380...480 V ATV930 variable speed drive wall mount - 37 kW, 380...480 V ATV930 variable speed drive wall mount - 45 kW, 380...480 V ATV950 variable speed drive wall mount - 30 kW, 380...480 V ATV950 variable speed drive wall mount - 37 kW, 380...480 V ATV950 variable speed drive wall mount - 45 kW, 380...480 V
Sale per indivisible quantity	1
Electrical connection	Terminal block, connection capacity: 50 mm² / 1 AWG

Complementary

Maximum motor cable length	500 M unshielded cable 300 M shielded cable
DV/dt	3000 V/µs max at 200...240 V 3000 V/µs max at 380...480 V
Thermal losses	92 W at 4 kHz
Maximum output frequency	100 Hz
Ambient air temperature for operation	-10…50 °C (without current derating) 50…60 °C (with current derating 1.5 % per °C)
Operating altitude	0...1000 m without current derating 1000...4000 m with current derating 1 % per 100 m
Width	300 Mm
Height	610 Mm

Depth	245 Mm
Net weight	19 Kg

Environment

IP degree of protection	IP20 IP21 (with kit VW3A53905)
Ambient air temperature for storage	-40…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	40.000 Cm
Package 1 Width	40.000 Cm
Package 1 Length	75.000 Cm
Package 1 Weight	24.000 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised