Product data sheet
Characteristics

VW3A7604R20
braking resistor - 27 ohm - 400 W - cable 2 m - IP65



Main

Range of product	Lexium Altivar
Range compatibility	Lexium 15 Lexium 52 Lexium 32i Lexium 32 Lexium 05 Lexium 28 Easy Lexium 16
Product compatibility	Motion servo drive LXM16D at 0.75 kW, 200...230 V, single phase[RETURN]Motion servo drive
Product or component type	Braking resistor
Ohmic value	27 Ohm

Complementary

Energy peak	10500 J at 480 V 11400 J at 400 V 18100 J at 230 V 25500 J at 115 V
Continuous power	400 W
Protection type	Thermal protection via the servo drive
Net weight	1.47 Kg
Cable length	2 M

Environment

IP degree of protection	IP65
Ambient air temperature for storage	-25…85 °C
Ambient air temperature for operation	0…50 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 Cm
Package 1 Width	12.500 Cm
Package 1 Length	39.500 Cm
Package 1 Weight	1.614 Kg
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Height	26.000 Cm
Package 2 Width	22.000 Cm

Package 2 Length	42.000 Cm
Package 2 Weight	9.968 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	108
Package 3 Height	95.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	199.420 Kg

Offer Sustainability

REACh free of SVHC	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised