
Product data sheet
Characteristics

VW3A7735
braking resistor, Altivar, 8Ohms, 1.1kW, IP20



Main

Range of product	Altivar
Range compatibility	Altivar Process ATV900 Altivar Machine ATV340 Altivar Machine ATV320
Product or component type	Braking resistor
Ohmic value	8 Ohm
[Ue] rated operational voltage	24 V DC 250 V AC

Complementary

Product compatibility	Variable speed drive ATV930 wall mount 55 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 15 kW 200...240 V light cycle Variable speed drive ATV950 wall mount 55 kW 380...480 V light cycle Variable speed drive ATV930 wall mount 15 kW 200...240 V medium cycle Variable speed drive ATV340 45 kW 380...480 V light cycle Variable speed drive ATV320 11 kW 200...240 V
Duty cycle	Light cycle (heavy duty) <0.8 s braking with 150 % braking torque for a 40 s cycle Light cycle (normal duty) <0.8 s braking with 120 % braking torque for a 40 s cycle Medium cycle (normal duty) <4 s braking with 135 % braking torque for a 40 s cycle Medium cycle (heavy duty) <4 s braking with 165 % braking torque for a 40 s cycle
Average power available	1.1 KW at 50 °C
Electrical connection	Terminal, connection capacity: <= 35 mm² / 3 AWG for drive terminal, connection capacity: <= 4 mm² / 10 AWG for temperature control switch
Protection type	Thermal protection via drive or temperature control switch at 120 °C
Width	190 Mm
Height	640 Mm
Depth	180 Mm
Net weight	4.5 Kg

Environment

IP degree of protection	IP20
Ambient air temperature for storage	-25…70 °C
Ambient air temperature for operation	0…50 °C
Product certifications	UL[RETURN]CE[RETURN]EAC[RETURN]UKCA[RETURN]RoHS

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.000 Cm
Package 1 Width	20.000 Cm
Package 1 Length	65.000 Cm

Package 1 Weight	5.342 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	6
Package 2 Height	75.000 Cm
Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	40.552 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised