Product data sheet
Characteristics

VW3A7743
braking resistor, Altivar, 16Ohms, 1.9kW, IP20



Main

Range of product	Altivar
Range compatibility	Altivar Machine ATV340 Altivar Process ATV900 Easy Altivar 310
Product or component type	Braking resistor
Ohmic value	16 Ohm
[Ue] rated operational voltage	24 V DC 250 V AC

Complementary

Product compatibility	Variable speed drive ATV930 wall mount 18.5 kW 380...480 V medium cycle Variable speed drive ATV930 wall mount 22 kW 380...480 V medium cycle Variable speed drive ATV930 wall mount 30 kW 380...480 V medium cycle Variable speed drive ATV950 wall mount 18.5 kW 380...480 V medium cycle Variable speed drive ATV950 wall mount 22 kW 380...480 V medium cycle Variable speed drive ATV950 wall mount 30 kW 380...480 V medium cycle Variable speed drive ATV930 wall mount 5.5 kW 200...240 V severe cycle Variable speed drive ATV340 15 kW 380...480 V medium cycle Variable speed drive ATV340 18 kW 380...480 V medium cycle Variable speed drive ATV340 22 kW 380...480 V medium cycle Variable speed drive ATV930 22 kW 500...690 V medium cycle Variable speed drive ATV930 30 kW 500...690 V medium cycle Variable speed drive ATV930 37 kW 500...690 V medium cycle Variable speed drive ATV930 32 hp 600 V medium cycle Variable speed drive ATV930 40 hp 600 V medium cycle Variable speed drive ATV930 50 hp 600 V medium cycle
Duty cycle	Severe cycle (heavy duty) <54 s braking with 100 % braking torque for a 120 s cycle Medium cycle (normal duty) <4 s braking with 135 % braking torque for a 40 s cycle Medium cycle (heavy duty) <4 s braking with 165 % braking torque for a 40 s cycle Severe cycle (heavy duty) <6 s braking with 165 % braking torque for a 120 s cycle
Average power available	1.9 KW at 50 °C
Electrical connection	Terminal, connection capacity: <= 10 mm² / 8 AWG for drive terminal, connection capacity: <= 2.5 mm² / 12 AWG for temperature control switch
Protection type	Thermal protection via drive or temperature control switch at 120 °C
Width	290 Mm
Height	570 Mm
Depth	180 Mm
Net weight	6.4 Kg

Environment

IP degree of protection	IP20
Ambient air temperature for storage	-25…70 °C
Ambient air temperature for operation	0…50 °C
Product certifications	UL[RETURN]CE[RETURN]EAC[RETURN]UKCA[RETURN]RoHS

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.500 Cm
Package 1 Width	58.000 Cm
Package 1 Length	30.500 Cm
Package 1 Weight	7.211 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	75.000 Cm
Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	37.632 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised