Product data sheet
Characteristics

VW3L40020
insert - 1 female/male M8, 4 pins- for 2 signals safe torque off safety function



Main

Range of product	Lexium integrated drive
Product or component type	Insert for communication interface
Accessory / separate part type	Connection accessories
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives

Complementary

Electrical connection	1 female connector M8 4 pins for for connection of signals for safe torque off 1 male connector M8 4 pins for for connection of signals for safe torque off
Kit composition	1 sealing insert 1 insert with connectors
Input/output type	2 STO signals
Net weight	0.027 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 Cm
Package 1 Width	4.0 Cm
Package 1 Length	6.0 Cm
Package 1 Weight	28.0 G
Unit Type of Package 2	S02
Number of Units in Package 2	75
Package 2 Height	15.0 Cm
Package 2 Width	30.0 Cm
Package 2 Length	40.0 Cm
Package 2 Weight	2.432 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold

EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised