Product data sheet
Characteristics

VW3L40210
insert - 2 female M8 for 2 I/O signals + 1 male M8 for safe torque off safety



Main

Range of product	Lexium integrated drive
Product or component type	Insert for communication interface
Accessory / separate part type	Connection accessories
Accessory / separate part category	Connection accessories
Accessory / separate part destination	For drives

Complementary

Electrical connection	1 male connector M8 4 pins for for connection of signals for safe torque off 2 female connectors M8 3 pins for for connection of 2 I/O signals
Kit composition	1 insert with connectors 1 sealing insert
Input/output type	2 I/O signals + 1 STO signal
Net weight	0.036 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 Cm
Package 1 Width	5.2 Cm
Package 1 Length	9.0 Cm
Package 1 Weight	36.0 G
Unit Type of Package 2	S01
Number of Units in Package 2	30
Package 2 Height	15.0 Cm
Package 2 Width	15.0 Cm
Package 2 Length	40.0 Cm
Package 2 Weight	1.242 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold

EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised