# Product data sheet
## Characteristics

# VW3M4A12
motion servo drive, Easy Lexium 16, CN1 adapter tool set with 24V PTI cable



## Main

| | |
|---|---|
| Range of product | Easy Lexium 16 |
| Accessory / separate part category | Spare part |
| Product or component type | Adaptor tool set |

## Complementary

| | |
|---|---|
| Device application | Connection of control with 24 V PTI |
| Kit composition | 1 cordset<br>1 interface module |
| Product compatibility | Motion servo drive LXM16D at 0.1 kW, 200...230 V, single phase<br>Motion servo drive LXM16D at 0.2 kW, 200...230 V, single phase<br>Motion servo drive LXM16D at 0.4 kW, 200...230 V, single phase<br>Motion servo drive LXM16D at 0.75 kW, 200...230 V, single phase<br>Motion servo drive LXM16D at 1 kW, 200...230 V, single phase<br>Motion servo drive LXM16D at 1.5 kW, 200...230 V, single phase |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 30.0 Cm |
| Package 1 Width | 32.0 Cm |
| Package 1 Length | 6.0 Cm |
| Package 1 Weight | 460.0 G |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 2 |
| Package 2 Height | 15.0 Cm |
| Package 2 Width | 15.0 Cm |
| Package 2 Length | 40.0 Cm |
| Package 2 Weight | 1120.0 G |

## Offer Sustainability

| | |
|---|---|
| REACh free of SVHC | Yes |
| Sustainable packaging | No |
| Packaging made with recycled cardboard | No |
| Packaging without single use plastic | No |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| Take-back | No |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : End of commerc. announced

## VW3M4A12 is replaced by the following product range:



165194762

Schneider Electric's new servo drive Lexium 18 is used in combination with the BCH18 motor to achieve stability, reliabil

Substitution date: |