Product data sheet
Characteristics

VW3M5101R200
power cable - between servomotor BDH;BSH and servodrive - 4x1.5mmÂ²+2x1mmÂ² - 20m



Main

Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessories
Product compatibility	Servo motor BMH, 1 motor stacks (70 mm) Servo motor BMH, 2 motor stacks (70 mm) Servo motor BMH, 3 motor stacks (70 mm) Servo motor BMH, 1 motor stacks (100 mm) Servo motor BMH, 2 motor stacks (100 mm) Servo motor BMH, 3 motor stacks (100 mm) Servo motor BMH, 1 motor stacks (140 mm) Servo motor BSH, 1 motor stacks (55 mm) Servo motor BSH, 2 motor stacks (55 mm) Servo motor BSH, 3 motor stacks (55 mm) Servo motor BSH, 1 motor stacks (70 mm) Servo motor BSH, 2 motor stacks (70 mm) Servo motor BSH, 3 motor stacks (70 mm) Servo motor BSH, 1 motor stacks (100 mm) Servo motor BSH, 2 motor stacks (100 mm) Servo motor BSH, 3 motor stacks (100 mm) Servo motor BSH, 1 motor stacks (140 mm)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 05 Lexium 15 Lexium 32
Cable length	20 M
Cable composition	4 x 1.5 mm² + 2 x 1 mm²

Complementary

Electrical connection	Connector - industrial M23 for servo motor side Free end for servo drive side
Net weight	4.51 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.600 Cm
Package 1 Width	41.500 Cm
Package 1 Length	45.500 Cm
Package 1 Weight	4.452 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	20
Package 2 Height	75.000 Cm

Package 2 Width	60.000 Cm
Package 2 Length	80.000 Cm
Package 2 Weight	105.580 Kg

Offer Sustainability

Total lifecycle Carbon footprint	648 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	24.7339485139
Carbon footprint of the manufacturing phase [A1 to A3]	25 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5713058575
Carbon footprint of the distribution phase [A4]	0.6 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.0022478697
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	618.04
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	618 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	4.2002681259
Carbon footprint of the end-of-life phase [C1 to C4]	4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	648
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised