Product data sheet
Characteristics

VW3M5D1AR50
power cable 5m shielded 4x 0,82mm², BCH2 leads connection



Main

Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessories
Product compatibility	Servo motor BCH2 at 50 W (40 mm) (without brake) Servo motor BCH2 at 100 W (40 mm) (without brake) Servo motor BCH2 at 200 W (60 mm) (without brake) Servo motor BCH2 at 400 W (60 mm) (without brake) Servo motor BCH2 at 400 W (80 mm) (without brake) Servo motor BCH2 at 750 W (80 mm) (without brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	5 M

Complementary

Electrical connection	Free end for servo drive side Connector - Molex 4-pin for servo motor side
AWG gauge	4 x 18 AWG
Net weight	0.45 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.600 Cm
Package 1 Width	28.400 Cm
Package 1 Length	34.200 Cm
Package 1 Weight	700.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	5
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	3.816 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised