Product data sheet
Characteristics

VW3M5D6AR50
power cable 5m shielded 4x 6mm², BCH2 MIL connector



Commercial status
End of Commercialisation : APR 21, 2026

⚠ End of Commercialisation

Main

Range of product	Lexium 28
Product or component type	Power cable
Accessory / separate part type	Preassembled power cordset
Accessory / separate part category	Connection accessories
Product compatibility	Servo motor BCH2 at 3000 W (180 mm) (without brake) Servo motor BCH2 at 3500 W (180 mm) (without brake) Servo motor BCH2 at 4500 W (180 mm) (without brake)
Accessory / separate part destination	Between servo motor and servo drive
Range compatibility	Lexium 28
Cable length	5 M

Complementary

Electrical connection	Free end for servo drive side Connector - MIL big for servo motor side
AWG gauge	4 x 10 AWG
Net weight	3.4 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.000 Cm
Package 1 Width	39.000 Cm
Package 1 Length	39.000 Cm
Package 1 Weight	2.548 Kg
Unit Type of Package 2	S04
Number of Units in Package 2	5
Package 2 Height	30.000 Cm
Package 2 Width	40.000 Cm
Package 2 Length	60.000 Cm
Package 2 Weight	13.570 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commerc. - Block