Product data sheet
Characteristics

BMXDRA0805
Discrete output module, Modicon X80, 8 NO relay outputs, 24 to 240V AC / 24V DC



Commercial status
End of Commercialisation :

⚠ End of Commercialisation

Main

Range of product	Modicon X80
Product or component type	Discrete output module

Complementary

Minimum switching current	10 MA 5 V DC
Response time on output	< 10 ms activation < 8 ms deactivation
Insulation resistance	> 10 MOhm 500 V DC
MTBF reliability	2119902 H
Net weight	0.145 Kg

Environment

IP degree of protection	IP20
Protective treatment	Standard version
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Dielectric strength	2000 V AC at 50/60 Hz 1 min
Relative humidity	5…95 % at 55 °C without condensation
Environmental characteristic	Corrosion resistance Dust resistant

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 Cm
Package 1 Width	11.0 Cm
Package 1 Length	12.0 Cm
Package 1 Weight	177.0 G

Offer Sustainability

REACh free of SVHC	Yes
Mercury free	Yes
Sustainable packaging	No
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, w

Contractual warranty

Warranty (in months)	18

Product Life Status : Post commercialisation

BMXDRA0805 may be replaced by any of the following products:



BMXDRA0815

discrete output module, Modicon X80, 8 NO relay outputs, 24 to 240V AC, 24 to 125V DC

Qty 1

Substitution date: |