Product data sheet
Characteristics

9422A1
Operating mechanism, flange mounted, variable depth, handle mechanism, 6in handle, NEMA 1, 3R, 4, 12 enclosure



Main

Product or component type	Handle Mechanism
Product destination	Disconnect switches (30...200 A) All circuit breaker mechanisms

Complementary

Specificity of operator	Variable depth
Product destination	All circuit breaker mechanisms disconnect switches (30...200 A)
Product compatibility	NEMA 1/3/3R/4/12 enclosures
Length	152.4 Mm
Net weight	1.26 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.572 Cm
Package 1 Width	9.652 Cm
Package 1 Length	23.876 Cm
Package 1 Weight	1.247 Kg
Unit Type of Package 2	PAL
Number of Units in Package 2	300
Package 2 Height	101.600 Cm
Package 2 Width	101.600 Cm
Package 2 Length	121.920 Cm
Package 2 Weight	381.017 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes

REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	"WARNING: This product can expose you to chemicals including: Lead and lead compounds, whic
POP Directive	No POPs
PVC free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised