Product data sheet
Characteristics

006920640
SLO Series outdoor light transmitter, SLO320, selectable outputs, 0-20,000 Lux



Main

Range of product	SLO300
Product or component type	Humidity sensor
Analogue output type	4...20 mA 0...10 V

Complementary

Former part number	6920640
Material	PA (polyamide): housing
Rated voltage	15…36 V DC 24 V +/- 10 % AC
Number of cables	2 cable(s)
Net weight	0.1 Kg
Width	85 Mm
Height	65 Mm
Luminous flux	0…20000 Lm
Device application	Outdoor reference
Light intensity measurement accuracy	+/- 5 %
Location	Outdoor
Range compatibility	Andover Continuum DMS Drayton Network 8000 Satchwell TAC I/A series TAC I/NET TAC Vista
Sensor signal category	Analogue
With override	No
Calibration certificate	Humidity: none
Targeted region	Europe Asia Pacific.

Environment

IP degree of protection	IP65
Standards	EN 50081-1 EN 50082-1
Ambient air temperature for operation	-20…70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.8 Cm
Package 1 Width	9.2 Cm
Package 1 Length	6.4 Cm
Package 1 Weight	151.3 G

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	F565ab1f-02d2-441f-9dff-67e55f1ae1be
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	24

Product Life Status : Commercialised