Product data sheet
Characteristics

170ENT11002
Modicon Momentum - Ethernet communication adaptor - 10 Mbit/s



Main

Range of product	Modicon Momentum automation platform
Product or component type	Ethernet TCP/IP communication adaptor

Complementary

Communication port protocol	Ethernet TCP/IP
Number of devices per segment	0…32
Transmission support medium	Shielded twisted pairs cable
Transmission rate	10 Mbit/s
Topology	Multidrop, star network
Cable length	1000 M
Local signalling	1 LED green for Ethernet network state (LAN) 1 LED green for module active (RUN)
Height	56 Mm
Width	178 Mm
Depth	259 Mm
Net weight	0.07 Kg

Environment

IP degree of protection	IP20
Protective treatment	TC
Marking	CE
Product certifications	UL[RETURN]FM Class 1 Division 2[RETURN]CSA
Standards	CSA FM Class 1 Division 2
Ambient air temperature for operation	0…60 °C
Ambient air temperature for storage	-40…85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.500 Cm
Package 1 Width	18.000 Cm
Package 1 Length	26.000 Cm
Package 1 Weight	251.000 G
Unit Type of Package 2	S03

Number of Units in Package 2	8
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	2.495 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	E618c0ab-f100-4cee-8aef-090f73ce1a54
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised