Product data sheet
Characteristics

170INT11000
Modicon Momentum - Interbus communication adaptor - twisted pair



Main

Range of product	Modicon Momentum automation platform
Product or component type	Interbus communication adaptor
Method of access	Continuous shift register Master/Slave

Complementary

Communication port protocol	Interbus generation SUPI 2
Fail state	Fail safe
Transmission support medium	Twisted pair
Transmission rate	500 kbit/s
Topology	Ring
Cable length	12800 M 400 M
Control parameter	CRC-16
Height	56 Mm
Width	178 Mm
Depth	259 Mm
Net weight	0.07 Kg

Environment

IP degree of protection	IP20
Protective treatment	TC
Marking	CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.600 Cm
Package 1 Width	17.800 Cm
Package 1 Length	26.000 Cm
Package 1 Weight	188.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	2.180 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	E618c0ab-f100-4cee-8aef-090f73ce1a54
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised