Product data sheet
Characteristics

3240211000
Current Transducer: Split Core, H321-S6, 30 mA (Max.) at 12 to 30 VDC, 0 to 300 A to 0 to 800 A (adjustable), 4 to 20mAdc

Commercial status
End of Commercialisation :

⚠ End of Commercialisation

Main

Range of product	High Current Series
Product or component type	Sensor
Sensor model	H321-S6
Type of measurement	AC current
Device application	Building automation systems
Current measurement accuracy	+/- 2 % of full scale above 6 A
Current measurement range	0...800 A
Sensor type	Current transducer, AC
AWG gauge	22 AWG...12 AWG
Network frequency	50...60 Hz
Opening width	61 Mm
Mounting support	Split core housing
Relative humidity	10…90 % RH, non-condensing
Analogue output type	4...20 mA
Output type	Analog
Product certifications	UL[RETURN]CE
Targeted region	Europe Asia Pacific.

Environment

Ambient air temperature for operation	-15…60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20 Cm
Package 1 Width	20 Cm
Package 1 Length	10 Cm
Package 1 Weight	150 G

Offer Sustainability

Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Post commercialisation