Product data sheet
Characteristics

9065SFC20
Overload Relay, Motor Logic, solid state overload relay, NEMA Size 00, 3 pole, 3A to 9A, 600VAC, separate mount



Main

Range of product	Motor Logic
Thermal overload type	Solid state

Complementary

NEMA size	00
Network number of phases	3 phases
Mounting support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	68.3 Mm
Width	82.8 Mm
Depth	99.1 Mm
Net weight	0.55 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 Cm
Package 1 Width	13.7 Cm
Package 1 Length	15.5 Cm
Package 1 Weight	440.0 G

Offer Sustainability

Recyclability potential, in %	42
Total lifecycle Carbon footprint	12 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	6.119170831278229
Carbon footprint of the manufacturing phase [A1 to A3]	6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.36527917482076944
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.23061402544817336
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5.069037029711683
Carbon footprint of the use phase [B2, B3, B4, B6]	5 kg CO2 eq.
Mercury free	Yes

Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.7141625120257316
Carbon footprint of the end-of-life phase [C1 to C4]	0.7 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	12
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	B65c2eed-aa1c-465f-bca3-a7c8f0610a23
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised