Product data sheet
Characteristics

9080FB3621J
Terminal block, Linergy, fuse holder, Class J, 60A, 600V, 3 pole

Local Stock Code: On Stock

Price*: 74.26 USD



Main

Range of product	9080FB
Product or component type	Fuse holder

Complementary

[In] rated current	60 A
[Ue] rated operational voltage	<= 600 V AC/DC
Fuse type	J
Fuse size	1.0625 x 2.375 in
Number of poles	3
Electrical connection	Box lugs
AWG gauge	14 AWG...2 AWG copper or aluminium
[Ics] rated service breaking capacity	200 KA conforming to UL 512
Product certifications	CSA file 70360 class 6225 01[RETURN]UL listed file E40747 CCN IZLT[RETURN]CE
Ambient air temperature for operation	-40…125 °C
Mounting support	Surface mount
Material	Thermoplastic: block
Wire stripping length	14.2875 Mm
Connections - terminals	Lugs 5.6 N.m for 3 AWG...2 AWG copper or aluminium wire Lugs 5.08 N.m for 6 AWG...4 AWG copper or aluminium wire Lugs 4.5 N.m for 8 AWG copper or aluminium wire Lugs 4.0 N.m for 12 AWG...10 AWG copper or aluminium wire Lugs 4.0 N.m for 14 AWG copper wire
Height	103.38 Mm
Width	119.89 Mm
Depth	53.09 Mm

Ordering and shipping details

Category	US1CTR121254
Discount Schedule	CTR1
GTIN	785901139669
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.588 Cm
Package 1 Width	10.414 Cm
Package 1 Length	12.192 Cm
Package 1 Weight	353.802 G
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	12.7 Cm
Package 2 Width	30.48 Cm
Package 2 Length	50.038 Cm
Package 2 Weight	7.199 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is k
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and neve

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised