# Product data sheet
## Characteristics

# 9422A2
Operating mechanism, flange mounted, variable depth, handle mechanism, 6in handle, NEMA 4X enclosure



## Main

| | |
|---|---|
| Product or component type | Handle Mechanism |
| Product destination | Disconnect switches (30...200 A) |

## Complementary

| | |
|---|---|
| Specificity of operator | Variable depth |
| Product destination | Disconnect switches (30...200 A) |
| Product compatibility | NEMA 4/4X enclosures |
| Length | 152.4 Mm |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.572 Cm |
| Package 1 Width | 9.652 Cm |
| Package 1 Length | 24.130 Cm |
| Package 1 Weight | 1.247 Kg |

## Offer Sustainability

| | |
|---|---|
| REACh free of SVHC | Yes |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| Sustainable packaging | Yes |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, w |
| PVC free | Yes |
| End of life manual availability | No need of specific recycling operations |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection a |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

| | |
|---|---|
| Product Life Status : | Commercialised |