Product data sheet
Characteristics

A9A26904
Auxiliary contact, Acti9 A9A, iOF, 1 C/O, 100mA to 6A, 24VAC to 415VAC, 24-130 VDC, bottom connection



Main

Range	Acti9
Product or component type	OC contact
Device short name	iOF
Signal contacts composition	1 C/O
[In] rated current	0.1…6 A at 24...240 V, AC 50/60 Hz 0.1…3 A at 415 V, AC 50/60 Hz 0.1…6 A at 24 V, DC 0.1…2 A at 48 V, DC 0.1…1.5 A at 60 V, DC 0.1…1 A at 130 V, DC
9 mm pitches	1
Standards	EN/IEC 60947-5-1 GB/T 14048.5
Product certifications	CE[RETURN]UKCA
Quality labels	EAC CCC CMIM

Complementary

Range compatibility	Acti9 iC60H RCBO[RETURN]Acti9 iC60H RCBO PoN[RETURN]Acti9 iC60H2 RCBO[RETURN
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	4 KV
Mounting mode	Clip-on
Mounting location	Left side of circuit-breaker
Mounting support	DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	86 Mm
Width	9 Mm
Depth	73 Mm
Net weight	32 G
Colour	White
Connections - terminals	Screw clamp terminal (bottom): 1 cable(s) 1…4 mm² - rigid Screw clamp terminal (bottom): 1 cable(s) 0.5…2.5 mm² - flexible Screw clamp terminal (bottom): 2 cable(s) 2.5 mm² - rigid Screw clamp terminal (bottom): 2 cable(s) 1.5 mm² - flexible with ferrule
Wire stripping length	10 Mm
Tightening torque	1 N.M bottom

Environment

IP degree of protection	IP20
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % at 55 °C
Ambient air temperature for operation	-35…70 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.100 Cm
Package 1 Width	8.000 Cm
Package 1 Length	9.300 Cm
Package 1 Weight	40.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.500 Cm
Package 2 Width	10.000 Cm
Package 2 Length	27.000 Cm
Package 2 Weight	565.000 G
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30.000 Cm
Package 3 Width	30.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	6.300 Kg

Offer Sustainability

Recyclability potential, in %	29
Total lifecycle Carbon footprint	0.9 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.24956059747568068
Carbon footprint of the manufacturing phase [A1 to A3]	0.2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.009188715242715289
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.01272019819894799
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.5311163929133567
REACh free of SVHC	Yes
Carbon footprint of the use phase [B2, B3, B4, B6]	0.5 kg CO2 eq.
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	0.0681808806294706
Carbon footprint of the end-of-life phase [C1 to C4]	0.1 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and Nickel (Metallic), which
OECD PFAS Regulation	No OECD PFAS Chemicals Present

POP Directive	No POPs
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	No
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised