Product data sheet
Characteristics

A9L08601
iPRD8r modular surge arrester - 3P + N - 350V - with remote transfert



Main

Range of product	IPRD
Range	Acti9
Product name	Acti9 iPRD
Product or component type	Surge arrester with pluggable cartridge
Device short name	iPRD8r
Device application	Distribution
Standards	EN 61643-11:2012 IEC 61643-11:2011
Product certifications	CE
Quality labels	NF KEMA-KEUR
Poles description	3P + N
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	TN-S TT

Complementary

Surge arrester class type	Type 2 + 3
Surge arrester technology	MOV + GDT
[Ue] rated operational voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
Nominal discharge current	Common mode: 2.5 kA (L/PE) Common mode: 2.5 kA (N/PE) Differential mode: 2.5 kA (L/N)
Maximum discharge current	Common mode: 8 kA L/PE Common mode: 8 kA N/PE Differential mode: 8 kA L/N
[Uoc] open circuit voltage	10 KV type 3 common mode N/PE 10 KV type 3 differential mode L/N
[Uc] maximum continuous operating voltage	Common mode: 260 V N/PE Common mode: 350 V L/PE Differential mode: 350 V L/N
Maximum [Up] voltage protection level	Common mode 1.1 kV type 3 N/PE Differential mode 1 kV type 2 L/N Differential mode 1.1 kV type 3 L/N Common mode 1.4 kV type 2 N/PE
[Ut] temporary overvoltage	337 V L/N 5 s withstand 1200 V N/PE 200 ms safe failure mode 442 V L/PE 5 s withstand
Disconnector device type	Associated circuit breaker iC60L 10 A curve C - Icu 25 kA[RETURN]Associated circuit breaker

Signalling circuit voltage	0.25 A/250 V AC 50/60 Hz
Mounting mode	Clip-on (DIN rail)
9 mm pitches	8
Height	85 Mm
Width	72 Mm
Depth	69 Mm
Net weight	0.421 Kg
Colour	White (RAL 9003)
Residual current	0.6 MA 0.003 MA
Connections - terminals	Tunnel type terminal (downside) 2.5…35 mm² Tunnel type terminal (upside) 2.5…35 mm²
Tightening torque	2.5 N.M
Compatibility code	IPRD8r

Environment

IK degree of protection	IK03 conforming to IEC 62262
Relative humidity	5…95 %
Operating altitude	2000 m
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.7 Cm
Package 1 Width	8.1 Cm
Package 1 Length	9.2 Cm
Package 1 Weight	455 G
Unit Type of Package 2	BB1
Number of Units in Package 2	3
Package 2 Height	8.3 Cm
Package 2 Width	10.2 Cm
Package 2 Length	27.7 Cm
Package 2 Weight	1.433 Kg
Unit Type of Package 3	S03
Number of Units in Package 3	27
Package 3 Height	30 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	13.359 Kg

Offer Sustainability

Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	A9614fa2-07f8-47d1-a2fe-e27b32003d8d
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
OECD PFAS Regulation	Item contains PFAS Chemicals
POP Directive	No POPs

Halogen-free status	Product contains halogen above thresholds
Silicone-free	No
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised