Product data sheet
Characteristics

A9L40421
iPRD40r modular surge arrester - 4P - IT - 460V - with remote transfert



Main

Range of product	IPRD
Range	Acti9
Product name	Acti9 iPRD
Product or component type	Surge arrester with pluggable cartridge
Device short name	iPRD40r
Device application	Distribution
Standards	EN 61643-11:2012 IEC 61643-11:2011
Product certifications	CE
Poles description	4P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	IT

Complementary

Surge arrester class type	Type 2
Surge arrester technology	MOV
[Ue] rated operational voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
Nominal discharge current	Common mode: 15 kA (L/PE) Common mode: 15 kA (N/PE)
Maximum discharge current	Common mode: 40 kA L/PE Common mode: 40 kA N/PE
[Uc] maximum continuous operating voltage	Common mode: 460 V L/PE
Maximum [Up] voltage protection level	Common mode 2.2 kV type 2 L/PE Common mode 2.2 kV type 2 N/PE
[Ut] temporary overvoltage	337 V L/N 5 s withstand 1455 V L/PE 200 ms safe failure mode 1455 V N/PE 200 ms safe failure mode
Short-circuit withstand	5 KA 415 V Ph/Ph
Disconnector device type	Associated fuse gG 63 A - Icu 15 kA Associated fuse gG 80 A - Icu 50 kA Associated circuit breaker iC60H 40 A curve C - Icu 15 kA Associated circuit breaker IC60N 40 A curve C - Icu 10 kA Associated circuit breaker NG125H 40 A curve C - Icu 36 kA Associated circuit breaker NG125L 40 A curve C - Icu 50 kA Associated circuit breaker NG125N 40 A curve C - Icu 25 kA
Signalling circuit voltage	0.25 A/250 V AC 50/60 Hz
Mounting mode	Clip-on (DIN rail)
9 mm pitches	8
Height	85 Mm

Width	72 Mm
Depth	69 Mm
Net weight	450 G
Colour	White (RAL 9003)
Residual current	0.6 MA
Connections - terminals	Tunnel type terminal (top or bottom) 2.5…25 mm² rigid Tunnel type terminal (top or bottom) 4…16 mm² flexible Tunnel type terminal (top or bottom) 4…16 mm² flexible with ferrule
Wire stripping length	14 Mm
Tightening torque	3.5 N.M
Targeted country	All
Compatibility code	IPRD40r

Environment

Relative humidity	5…95 %
Operating altitude	2000 m
Ambient air temperature for operation	-25…60 °C
Ambient air temperature for storage	-40…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.000 Cm
Package 1 Width	8.000 Cm
Package 1 Length	9.200 Cm
Package 1 Weight	491.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	3
Package 2 Height	8.500 Cm
Package 2 Width	10.400 Cm
Package 2 Length	27.600 Cm
Package 2 Weight	1.539 Kg
Unit Type of Package 3	S03
Number of Units in Package 3	27
Package 3 Height	30.000 Cm
Package 3 Width	30.000 Cm
Package 3 Length	40.000 Cm
Package 3 Weight	14.424 Kg

Offer Sustainability

Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	A9614fa2-07f8-47d1-a2fe-e27b32003d8d
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
OECD PFAS Regulation	Item contains PFAS Chemicals
POP Directive	No POPs
Halogen-free status	Product contains halogen above thresholds
End of life manual availability	No need of specific recycling operations

Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised