Product data sheet
Characteristics

ATS01N106FT
soft starter for asynchronous motor, Altistart 01, ATS01, 6A, 110 to 480V, 0.75 to 3kW



Main

Range of product	Altistart 01
Product destination	Asynchronous motors
Product or component type	Soft starter
Product specific application	Simple machine
Device short name	ATS01
Network number of phases	1 phase
[Us] rated supply voltage	110...480 V - 10...10 %
Motor power kW	3 KW, 3 phases at 400 V 0.75 KW, 3 phases at 230 V 1.1 KW, 3 phases at 230 V 2.2 KW, 3 phases at 400 V 0.75 KW, 1 phase at 230 V
Motor power hp	1 Hp, 3 phases at 230 V 2 Hp, 3 phases at 460 V 3 Hp, 3 phases at 460 V 0.5 Hp, 3 phases at 210 V 1.5 Hp, 3 phases at 230 V
IcL starter rating	6 A
Utilisation category	AC-53B conforming to EN/IEC 60947-4-2
Current consumption	30 A at nominal load
Type of start	Start with voltage ramp
Power dissipation in W	1 W at full load and at end of starting 31 W in transient state

Complementary

Assembly style	With heat sink
Function available	Integrated bypass
Supply voltage limits	99…528 V
Supply frequency	50...60 Hz - 5...5 %
Network frequency	47.5...63 Hz
Output voltage	<= power supply voltage
[Uc] Control circuit voltage	110 V AC +/- 10 % at 30 mA 24 V AC/DC +/- 10 % at 25 mA 240 V AC +/- 10 % at 65 mA
Starting time	1 s / 100 5 s / 20 Adjustable from 1 to 5 s
Starting torque	30...80 % of starting torque of motor connected directly on the line supply
Discrete output current	2 A DC-13 3 A AC-15
Tightening torque	0.8 N.M

Electrical connection	Cage type connector - rigid 1 2.5 mm² 14 AWG control circuit Cage type connector - rigid with cable end 1 2.5 mm² 14 AWG power circuit Cage type connector - rigid without cable end 2 1 mm² 17 AWG control circuit Cage type connector - rigid without cable end 2 1 mm² 17 AWG power circuit Cage type connector - flexible with cable end 1 2.5 mm² 14 AWG control circuit Cage type connector - flexible with cable end 1 2.5 mm² 14 AWG power circuit Cage type connector - flexible without cable end 1 2.5 mm² 14 AWG control circuit Cage type connector - flexible without cable end 1 2.5 mm² 14 AWG power circuit Cage type connector - flexible with cable end 2 0.75 mm² 18 AWG control circuit Cage type connector - flexible with cable end 2 0.75 mm² 18 AWG power circuit Cage type connector - flexible without cable end 2 1 mm² 17 AWG control circuit Cage type connector - flexible without cable end 2 1 mm² 17 AWG power circuit
Marking	CE
Operating position	Vertical +/- 10 degree
Height	100 Mm
Width	23 Mm
Depth	100 Mm
Net weight	0.16 Kg
Compatibility code	ATS01N1
Power range	0.55…1 KW at 200…240 V 3 phases 1.1…2 KW at 380…440 V 3 phases 0.55…1 KW at 200…240 V 1 phase 1.1…2 KW at 200…240 V 3 phases 2.2…3 KW at 380…440 V 3 phases
Motor starter type	Soft starter

Environment

Electromagnetic compatibility	Conducted and radiated emissions level B conforming to CISPR 11 Conducted and radiated emissions level B conforming to IEC 60947-4-2 Damped oscillating waves level 3 conforming to IEC 61000-4-12 Electrostatic discharge level 3 conforming to IEC 61000-4-2 EMC immunity level 3 conforming to EN 50082-1 EMC immunity level B conforming to EN 50082-2 Harmonics level 3 conforming to IEC 1000-3-2 Harmonics level 3 conforming to IEC 1000-3-4 Immunity to conducted interference caused by radio-electrical fields level 3 conforming to IEC 610 Immunity to electrical transients level 4 conforming to IEC 61000-4-4 Immunity to radiated radio-electrical interference level 3 conforming to IEC 61000-4-3 Micro-cuts and voltage fluctuation conforming to IEC 61000-4-11 Voltage/Current impulse level 3 conforming to IEC 61000-4-5
Standards	EN/IEC 60947-4-2
Product certifications	C-Tick[RETURN]CCC[RETURN]CSA[RETURN]UL[RETURN]GOST
IP degree of protection	IP20
Pollution degree	2 conforming to EN/IEC 60947-4-2
Vibration resistance	1 gn (f= 13…150 Hz) conforming to EN/IEC 60068-2-6 1.5 mm peak to peak (f= 3…13 Hz) conforming to EN/IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to EN/IEC 60068-2-27
Relative humidity	5…95 % without condensation or dripping water conforming to EN/IEC 60068-2-3
Ambient air temperature for operation	-10…40 °C (without derating) 40…50 °C (with current derating of 2 % per °C)
Ambient air temperature for storage	-25…70 °C conforming to EN/IEC 60947-4-2
Operating altitude	<= 1000 m without derating > 1000 m with current derating of 2.2 % per additional 100 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.5 Cm
Package 1 Width	10.3 Cm
Package 1 Length	10.5 Cm
Package 1 Weight	178.0 G
Unit Type of Package 2	S02
Number of Units in Package 2	36
Package 2 Height	15.0 Cm
Package 2 Width	30.0 Cm

Package 2 Length	40.0 Cm
Package 2 Weight	6.715 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, w
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised