Product data sheet
Characteristics

C10F2TM080
Circuit breaker, ComPacT NSX100F AC/DC, 18kA/415VAC, 2 poles, TMD trip unit 80A



Main

Range	ComPacT
Product name	ComPacT NSX
Device short name	NSX100F
Product or component type	Circuit breaker
Device application	Distribution
Poles description	2P
Protected poles description	2D
[In] rated current	80 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz 500 V DC
Network type	AC DC
Network frequency	50/60 Hz
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Utilisation category	Category A
Breaking capacity	36 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 18 KA Icu at 380/415 V AC 50/60 Hz 1P conforming to IEC 60947-2 15 KA Icu at 440 V AC 50/60 Hz 1P conforming to IEC 60947-2 10 KA Icu at 500/525 V AC 50/60 Hz 2P conforming to IEC 60947-2 5 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 36 KA Icu at 250 V DC 50/60 Hz 1 pole conforming to IEC 60947-2 36 KA Icu at 500 V DC 50/60 Hz 2 poles in series conforming to IEC 60947-2
Breaking capacity code	F 18 kA 415 V AC
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Trip unit protection functions	LI
Control type	Toggle
Mounting mode	Fixed

Complementary

[Ui] rated insulation voltage	750 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	8 KV conforming to IEC 60947-2
[Ics] rated service breaking capacity	36 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 18 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 15 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2 10 KA at 500/525 V AC 50/60 Hz conforming to IEC 60947-2 5 KA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 36 KA at 250 V DC 50/60 Hz conforming to IEC 60947-2 36 KA at 500 V DC 50/60 Hz conforming to IEC 60947-2
Mechanical durability	20000 Cycles
Electrical durability	20000 Cycles at 277 V In/2 10000 Cycles at 277 V In
Power dissipation per pole	8.77 W
Mounting support	Backplate
Mounting position	Horizontal and vertical Flat on the back
Upside connection	Front
Downside connection	Front
Connection pitch	35 Mm
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	80 A at 40 °C
Long time pick-up adjustment type Ir	Fixed
Long time pick-up adjustment range	1 x In
Long time delay adjustment type	Fixed
Instantaneous pick-up adjustment type Ii	Fixed
Instantaneous pick-up adjustment range	640 A
Earth-leakage protection	Without
Width	70 Mm

Height	161 Mm
Depth	86 Mm
Net weight	1.2 Kg

Environment

Standards	EN/IEC 60947-2
Overvoltage category	III
Electrical shock protection class	Class II on front face
Pollution degree	3 conforming to IEC 60664-1
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-50…85 °C
Relative humidity	0…95 %
Operating altitude	0...2000 m without derating 2000 m...5000 m with derating

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.900 Cm
Package 1 Width	13.000 Cm
Package 1 Length	17.600 Cm
Package 1 Weight	1.241 Kg
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	15.410 Kg

Offer Sustainability

Recyclability potential, in %	54
Total lifecycle Carbon footprint	104 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	6.855047619047619
Carbon footprint of the manufacturing phase [A1 to A3]	7 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.35773121477162295
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.10474932458697765
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	94.44188160000002
Carbon footprint of the use phase [B2, B3, B4, B6]	94 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	2.09806185617104
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	104
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	3874e08b-fcb8-4aa9-87c4-d36abebf2833
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, w
Halogen-free status	Product contains halogen above thresholds

PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised