# Product data sheet
## Characteristics

# C10F3MA025
Circuit breaker, ComPacT NSX100F, 36kA/415VAC, 3 poles, MA trip unit 25A



## Main

| | |
|---|---|
| Range | ComPacT |
| Product name | ComPacT NSX |
| Device short name | NSX100F |
| Product or component type | Circuit breaker |
| Device application | Motor protection |
| Poles description | 3P |
| Protected poles description | 3D |
| [In] rated current | 25 A at 65 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Suitability for isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation category | Category A |
| Breaking capacity | 85 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>25 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>22 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>8 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>85 KA Icu at 240 V AC 50/60 Hz conforming to UL 60947-4-1<br>25 KA Icu at 480 V AC 50/60 Hz conforming to UL 60947-4-1<br>10 KA Icu at 600 V AC 50/60 Hz conforming to UL 60947-4-1 |
| Breaking capacity code | F 36 kA 415 V AC |
| Trip unit name | MA |
| Trip unit technology | Magnetic |
| Trip unit protection functions | I |
| Control type | Toggle |
| Mounting mode | Fixed |

## Complementary

| | |
|---|---|
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 KV |
| [Ics] rated service breaking capacity | 85 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>36 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>12 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>11 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>4 KA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability | 50000 Cycles |
| Electrical durability | 50000 Cycles at 440 V In/2<br>30000 Cycles at 440 V In<br>20000 Cycles at 690 V In/2<br>10000 Cycles at 690 V In |
| Power dissipation per pole | 1.04 W |
| Mounting support | Backplate |
| Mounting position | Horizontal and vertical<br>Flat on the back |
| Upside connection | Front |
| Downside connection | Front |
| Connection pitch | 35 Mm |
| Protection type | I : for short-circuit protection (magnetic) |
| Trip unit rating | 25 A at 65 °C |
| Short-time pick-up adjustment type Isd | Adjustable 9 settings |
| [Isd] short-time pick-up adjustment range | 6...14 x In |
| Instantaneous pick-up adjustment type Ii | Adjustable 9 settings |
| Instantaneous pick-up adjustment range | 6...14 x In |
| Earth-leakage protection | Without |
| Number of slots | 5 slot(s) |
| Width | 105 Mm |

| | |
|---|---|
| Height | 161 Mm |
| Depth | 86 Mm |
| Net weight | 2.05 Kg |

## Environment

| | |
|---|---|
| Standards | EN/IEC 60947-2 |
| Overvoltage category | III |
| Electrical shock protection class | Class II on front face |
| Pollution degree | 3 conforming to IEC 60664-1 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Ambient air temperature for operation | -25…70 °C |
| Ambient air temperature for storage | -50…85 °C |
| Relative humidity | 0…95 % |
| Operating altitude | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 14 Cm |
| Package 1 Width | 11.5 Cm |
| Package 1 Length | 19 Cm |
| Package 1 Weight | 2.23 Kg |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 8 |
| Package 2 Height | 30 Cm |
| Package 2 Width | 30 Cm |
| Package 2 Length | 40 Cm |
| Package 2 Weight | 17.84 Kg |

## Offer Sustainability

| | |
|---|---|
| Recyclability potential, in % | 54 |
| Total lifecycle Carbon footprint | 34 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 12.318095238095237 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 12 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.6428207968901846 |
| Carbon footprint of the distribution phase [A4] | 0.6 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.18822803692905732 |
| Carbon footprint of the installation phase [A5] | 0.2 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 16.762680000000003 |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 17 kg CO2 eq. |
| Mercury free | Yes |
| Sustainable packaging | Yes |
| Carbon footprint of the end-of-life phase [C1 to C4] | 3.7700869776482016 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 4 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 34 |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| SCIP Number | 3874e08b-fcb8-4aa9-87c4-d36abebf2833 |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant By Exemption |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, w |
| Halogen-free status | Product contains halogen above thresholds |

| | |
|---|---|
| PVC free | Yes |
| End of life manual availability | End Of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : Commercialised