Product data sheet
Characteristics

C254200D1S
Switch disconnector, ComPacT NSX200NA DC PV, 4 poles, fixed, 200A rating, 1000V



Main

Range	ComPacT
Product name	ComPacT NSX DC PV
Device short name	NSX200NA DC PV
Product or component type	Switch disconnector
Device application	Photovoltaic
Poles description	4P
[Ith] conventional free air thermal current	150 A at 65 °C
[Ie] rated operational current	DC-22A: 200 A DC 1000 V
[Ue] rated operational voltage	1000 V DC
Network type	DC
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Utilisation category	DC-22A
Breaking capacity code	NA
Contact position indicator	Yes
Visible break	No
Mounting mode	Fixed
[Icw] rated short-time withstand current	2.5 KA during 1 s
[Icm] rated short-circuit making capacity	2.5 KA switch-disconnector alone
Control type	Toggle
[Ui] rated insulation voltage	1000 V DC
[Uimp] rated impulse withstand voltage	8 KV

Complementary

Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	35 Mm
Mechanical durability	10000 Cycles
Electrical durability	1000 Cycles 1000 V DC In
Width	140 Mm
Height	161 Mm
Depth	86 Mm
Net weight	2.8 Kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-50…85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.500 Cm
Package 1 Width	14.500 Cm
Package 1 Length	19.000 Cm
Package 1 Weight	2.606 Kg
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	16.056 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	48
Package 3 Height	45.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	140.448 Kg

Offer Sustainability

Recyclability potential, in %	59
Total lifecycle Carbon footprint	402 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	17.122733406774994
Carbon footprint of the manufacturing phase [A1 to A3]	17 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3407752299641972
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.22263321399063618
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	379.1494193548388
Carbon footprint of the use phase [B2, B3, B4, B6]	379 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	5.330063068025337
Carbon footprint of the end-of-life phase [C1 to C4]	5 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	402
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	3874e08b-fcb8-4aa9-87c4-d36abebf2833
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Halogen-free status	Product contains halogen above thresholds
PVC free	Yes

Silicone-free	No
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised