Product data sheet
Characteristics

CCT15233
Acti9 - MINp - silent electronic timer - adjustable from 0.5 to 20 minutes



Main

Range	Acti9
Product name	Acti9 MIN
Device short name	MINp
Product or component type	Silent electronic timer
Product compatibility	Mechanical compatibility with electrical comb busbars
Function available	Switch-off warning
Colour tint	White (RAL 9003)

Complementary

Device application	Building
Load type	Fluocompact lampconventional ballast 1500 VA Fluorescent lamp 22 x electronic ballast 23 W 230 V AC halogen lamp 3600 W 230 V AC incandescent lamp 3600 W Fluorescent lamp 24 x electronic ballast 15 W Fluorescent lamp 27 x electronic ballast 11 W Fluorescent lamp 34 x electronic ballast 7 W Dual mounted fluorescent tubeconventional ballast 3600 VA Fluorescent tubeelectronic ballast 1000 VA Non-corrected fluorescent tubeconventional ballast 3600 VA Parallel-corrected fluorescent tubeconventional ballast 1200 VA Serial-corrected fluorescent tubeconventional ballast 3600 VA
Power consumption in VA	6 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Time delay	Adjustable from 0.5 to 20 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals - <= 6 mm²
Electrical insulation class	Class II
Width	18 Mm
Height	89 Mm
Depth	66 Mm
Net weight	103 G

Environment

Ambient air temperature for operation	-25…50 °C
IP degree of protection	IP20 B

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.2 Cm
Package 1 Width	7 Cm
Package 1 Length	10 Cm
Package 1 Weight	100 G
Unit Type of Package 2	S03
Number of Units in Package 2	130
Package 2 Height	30 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	13.877 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	5c23d91a-4c63-483e-b70a-45310671b035
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised