Product data sheet
Characteristics

CCT15369
Acti9 IC2000 outdoor (2 - 2000 lux) twilight switch



Main

Range	Acti9
Product name	Acti9 IC
Product or component type	Twilight switch
Device short name	IC2000
Provided equipment	Twilight sensor outdoor
Load type	Incandescent lamp: 2600 W Halogen lamp: 2600 W Non-corrected fluorescent tube: 2300 VA Serial-compensated fluorescent tube: 2300 VA Parallel compensated fluorescent lamp: 730 VA (80 µF) Compact fluorescent lamp: 170 W < 2 W LED lamp: 30 W >= 2 W LED lamp: 200 W

Complementary

Device application	Building
Number of channels	1
Maximum power consumption in W	0.5 W stand by
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Maximum switching current	10 A - 250 V AC pf = 0.6 16 A - 250 V AC pf = 1
Minimum switching current	10 MA 230 V AC 100 MA 24 V AC/DC
Electrical insulation class	Class II
Output type	Dry contact
Accuracy	+/- 0.25 s/day 25 °C
Contacts type and composition	1 NO
Time delay	20 s on 80 s off
Light intensity adjustment	2…2000 Lux
Connections - terminals	1 x 2.5 mm² screw terminals solid or flexible with sleeve 2 x 0.5…2.5 mm² screw terminals solid or flexible
Mounting support	TH35 DIN rail conforming to EN 60715
Height	85.5 Mm
Width	18 Mm
Depth	67 Mm
Net weight	111 G
Overvoltage category	Class 3
Marking	CE
Control type	By brightness detection

Environment

Ambient air temperature for operation	-30…55 °C
Ambient air temperature for storage	-30…70 °C
Relative humidity	90 %, non-condensing
IP degree of protection	IP20 IP55 (sensor)
Standards	EN 60669-2-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.500 Cm
Package 1 Width	8.000 Cm
Package 1 Length	10.500 Cm
Package 1 Weight	162.000 G
Unit Type of Package 2	S03
Number of Units in Package 2	40
Package 2 Height	30.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	6.890 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	320
Package 3 Height	45.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	66.120 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	5c23d91a-4c63-483e-b70a-45310671b035
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised