Product data sheet
Characteristics

CR1F400F7
TeSys F magnetic latching contactor - 3P(3 NO) - 400 A - 110 V AC/DC coil



⚠ End of Commercialisation

Commercial status
End of Commercialisation : AUG 15, 2026

Main

Range	TeSys
Product name	TeSys F
Product or component type	Magnetic latching contactor
Device short name	CR1F
Device application	Control
Contactor application	Resistive load Motor control
Utilisation category	AC-1 AC-3 AC-4
Poles description	3P
Pole contact composition	3 NO
[Ue] rated operational voltage	1000 V AC 25...200 Hz
[Ie] rated operational current	400 A (at <40 °C) at <= 440 V AC AC-3 500 A (at <40 °C) at <= 440 V AC AC-1 370 A (at <40 °C) at <= 440 V AC AC-4
Motor power kW	200 KW at 400 V AC 50/60 Hz (AC-4)
Control circuit type	AC at 50...400 Hz DC standard
[Uc] control circuit voltage	110 V AC 50...400 Hz 110 V DC
Irms rated making capacity	4500 A
Rated breaking capacity	4000 A at 220...440 V 3500 A at 500 V 1200 A at 1000 V 3000 A at 660/690 V
[Icw] rated short-time withstand current	3600 A 40 °C - 1 s 3600 A 40 °C - 5 s 3600 A 40 °C - 10 s 2400 A 40 °C - 30 s 1700 A 40 °C - 1 min 1200 A 40 °C - 3 min 1000 A 40 °C - 10 min
Associated fuse rating	400 A aM at <= 440 V 500 A BS88 at <= 440 V 500 A gG at <= 440 V
Average impedance	0.28 MOhm - Ith 500 A 50 Hz
[Ui] rated insulation voltage	1000 V conforming to IEC 60158-1 1000 V conforming to IEC 60947-4 1000 V conforming to BS 775 1500 V conforming to VDE 0110 group C

Power dissipation per pole	45 W AC-3 70 W AC-1
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 JIS C8201-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	CB Scheme[RETURN]UL[RETURN]CSA[RETURN]EAC[RETURN]CE[RETURN]UKCA
Connections - terminals	Lugs-ring terminals 2 cable(s) 150 mm² Bars 2 cable(s) - busbar cross section: 30 x 5 mm Power circuit: bolted connection
Tightening torque	35 N.M
Operating time	40...75 ms latching 50...100 ms unlatching
Mechanical durability	1 Mcycles
Maximum operating rate	120 Cyc/H 40 °C

Complementary

Control circuit voltage limits	Latching: 0.85...1.1 Uc Unlatching: 0.85...1.1 Uc
Average coil consumption	1600 VA AC 50...400 Hz latching 16 VA AC 50...400 Hz unlatching 1600 VA DC latching 16 VA DC unlatching

Environment

Protective treatment	TC
Ambient air temperature for operation	-15…70 °C
Ambient air temperature for storage	-60…80 °C
Operating altitude	3000 m without derating
Height	206 Mm
Width	213 Mm
Depth	219 Mm
Net weight	9.1 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.0 Cm
Package 1 Width	23.5 Cm
Package 1 Length	30.0 Cm
Package 1 Weight	9.28 Kg

Offer Sustainability

Recyclability potential, in %	95
Total lifecycle Carbon footprint	3 565 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	62.80696293224851
Carbon footprint of the manufacturing phase [A1 to A3]	63 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	3.426810412371508
Carbon footprint of the distribution phase [A4]	3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.027537467863151668
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3479.3680864228145
Carbon footprint of the use phase [B2, B3, B4, B6]	3 479 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	19.754330715608273
Carbon footprint of the end-of-life phase [C1 to C4]	20 kg CO2 eq.

Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	3565
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and c
SCIP Number	975ba4d0-bc82-40e2-8faa-6f6819f63b0c
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, wh
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : End of commercialisation