Product data sheet
Characteristics

GS2AH240
External rotary handle, TeSys GS, red handle, right side mounting, 2 positions I-O, IP65, for GS 100 to 400A IEC



Main

Range of product	TeSys
Range	TeSys
Device short name	GS2AH
Product or component type	Rotary handle
Range compatibility	TeSys TeSys GS GS2J TeSys TeSys GS GS2K TeSys TeSys GS GS2L TeSys TeSys GS GS2N TeSys TeSys GS GS2P TeSys TeSys GS GS2Q FuPact FuPacT GS GSB100 FuPact FuPacT GS GSC125 FuPact FuPacT GS GSD125 FuPact FuPacT GS GSB160 FuPact FuPacT GS GSB200 FuPact FuPacT GS GSB250 FuPact FuPacT GS GSD250 FuPact FuPacT GS GSB400 FuPact FuPacT GS GSD400
Type of operating handle	External right side
Handle colour	Red
Handle front plate colour	Yellow

Complementary

Marking	O-I
Rotary handle padlocking	Lockable in O position
[In] rated current	100 A 125 A 160 A 200 A 250 A 315 A 400 A
Standards	IEC
Net weight	0.24 Kg

Environment

IP degree of protection	IP65

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.000 Cm
Package 1 Width	10.000 Cm
Package 1 Length	18.000 Cm
Package 1 Weight	217.000 G
Unit Type of Package 2	S04
Number of Units in Package 2	40
Package 2 Height	30.000 Cm
Package 2 Width	40.000 Cm
Package 2 Length	60.000 Cm
Package 2 Weight	9.610 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the St
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised