Product data sheet
Characteristics

GS2AH430
External rotary handle, TeSys GS, black handle, front mounting, 2 positions I-O, NEMA 4-4X, for GS 30-400A UL



Main

Range of product	TeSys
Range	TeSys
Device short name	GS2AH
Product or component type	Rotary handle
Range compatibility	TeSys TeSys GS GS2EU TeSys TeSys GS GS2GU TeSys TeSys GS GS2JU TeSys TeSys GS GS2MU TeSys TeSys GS GS2QU
Type of operating handle	External frontal
Handle colour	Black
Handle front plate colour	Grey

Complementary

Marking	O-I
Rotary handle padlocking	With
[In] rated current	30 A 60 A 100 A 200 A 400 A
Standards	CSA UL
Net weight	0.24 Kg

Environment

NEMA degree of protection	NEMA 4X

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 Cm
Package 1 Width	18.0 Cm
Package 1 Length	18.0 Cm
Package 1 Weight	249.0 G
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	30.0 Cm

Package 2 Width	30.0 Cm
Package 2 Length	40.0 Cm
Package 2 Weight	5.458 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the St
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised