
Product data sheet
Characteristics

GV2G272
Linergy FT, Comb busbar, 63A, 2 tap-offs, 72mm pitch



Main

Range	Linergy
Product name	FT
Device short name	GV2G
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Range compatibility	TeSys GV2 TeSys K TeSys U TeSys Deca
Fixing mode	Terminals:
Number of tap-offs	2
[Ith] conventional free air thermal current	63 A

Complementary

Product certifications	CE[RETURN]cULus
[Ui] rated insulation voltage	690 V
Connection pitch	72 Mm
Width	116 Mm
Net weight	0.05 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.000 Cm
Package 1 Width	11.700 Cm
Package 1 Length	3.300 Cm
Package 1 Weight	46.000 G
Unit Type of Package 2	S01
Number of Units in Package 2	40
Package 2 Height	15.000 Cm
Package 2 Width	15.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	2.039 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised