Product data sheet
Characteristics

GV2RT14
Motor circuit breaker,TeSys Deca,3P,6-10A,thermal magnetic,screw clamp terminals,toggle handle



Main

Range	TeSys Deca
Product name	TeSys GV2
Product or component type	Motor circuit breaker
Device short name	GV2RT
Device application	Motor protection Transformer
Trip unit technology	Thermal-magnetic

Complementary

Poles description	3P
Network type	AC
Utilisation category	Category A conforming to IEC 60947-2 AC-3 conforming to IEC 60947-4-1 AC-3e conforming to IEC 60947-4-1
Network frequency	50/60 Hz conforming to IEC 60947-2
Motor power kW	1.5 KW at 220/230 V AC 50/60 Hz motor protection high peak current 2.2 KW at 220/230 V AC 50/60 Hz motor protection high peak current 3 KW at 400/415 V AC 50/60 Hz motor protection high peak current 4 KW at 400/415 V AC 50/60 Hz motor protection high peak current 4 KW at 440 V AC 50/60 Hz motor protection high peak current 4 KW at 500 V AC 50/60 Hz motor protection high peak current 5.5 KW at 500 V AC 50/60 Hz motor protection high peak current 5.5 KW at 690 V AC 50/60 Hz motor protection high peak current 7.5 KW at 690 V AC 50/60 Hz motor protection high peak current 2.5 KW at 230/240 V AC 50/60 Hz transformer protection 4 KW at 400/415 V AC 50/60 Hz transformer protection 5 KW at 400/415 V AC 50/60 Hz transformer protection 5 KW at 440 V AC 50/60 Hz transformer protection 5 KW at 500 V AC 50/60 Hz transformer protection 6.3 KW at 500 V AC 50/60 Hz transformer protection
Breaking capacity	100 KA Icu at 220/230 V AC 50/60 Hz conforming to IEC 60947-2 100 KA Icu at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 15 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 10 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 3 KA Icu at 690 V AC 50/60 Hz conforming to IEC 60947-2
Control type	Toggle
[In] rated current	10 A
Thermal protection adjustment range	6…10 A conforming to IEC 60947-2
Magnetic tripping current	200 A
[Ith] conventional free air thermal current	10 A conforming to IEC 60947-2
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2

[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-1
Power dissipation per pole	2.5 W
Mechanical durability	100000 Cycles
Electrical durability	100000 Cycles for AC-3 at 415 V In 100000 Cycles for AC-3e at 415 V In
Rated duty	Uninterrupted conforming to IEC 60947-4-1
Connections - terminals	Power circuit: screw clamp terminal 2 cable(s) 1…6 mm² - solid Power circuit: screw clamp terminal 2 cable(s) 1.5…6 mm² - flexible without cable end Power circuit: screw clamp terminal 2 cable(s) 1…4 mm² - flexible with cable end
Tightening torque	1.7 N.M - on screw clamp terminal
Fixing mode	35 mm symmetrical DIN rail: clipped Panel: screwed (with adaptor plate)
Mounting position	Horizontal Vertical
Width	45 Mm
Height	89 Mm
Depth	78.5 Mm

Environment

Standards	EN/IEC 60947-2 EN/IEC 60947-4-1
Product certifications	CB Scheme[RETURN]CE[RETURN]UKCA[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETU
IK degree of protection	IK04
IP degree of protection	IP20 conforming to IEC 60529
Climatic withstand	Conforming to IACS E10
Ambient air temperature for storage	-40…80 °C
Fire resistance	960 °C conforming to IEC 60695-2-11
Ambient air temperature for operation	-20…60 °C
Mechanical robustness	Shocks: 30 Gn for 11 ms Vibrations: 5 Gn, 5...150 Hz
Operating altitude	<= 2000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.700 Cm
Package 1 Width	9.500 Cm
Package 1 Length	8.500 Cm
Package 1 Weight	276.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	6.930 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	288
Package 3 Height	75.000 Cm
Package 3 Width	60.000 Cm
Package 3 Length	80.000 Cm
Package 3 Weight	92.872 Kg

Offer Sustainability

Recyclability potential, in %	49
Total lifecycle Carbon footprint	12 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.069590396794914
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.10422048542264055
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.05212458121202044
Carbon footprint of the installation phase [A5]	0.1 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	8.86395212531129
Carbon footprint of the use phase [B2, B3, B4, B6]	9 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.5730413800864925
Carbon footprint of the end-of-life phase [C1 to C4]	0.6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	12
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	26be41f9-3f94-42e0-8ac0-5c45e1766355
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony tr
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised