Product data sheet
Characteristics

GV4ADM1111
Auxiliary contact block, TeSys GV4, 2NO+2NC, SDx contact module for GV4PEM



Main

Range	TeSys
Device short name	GV4A
Product or component type	Auxiliary contact block
Product compatibility	GV4
Mounting location	Right side
Auxiliary contacts operation	Signalling
Pole contact composition	2 NO + 2 NC

Complementary

[Ui] rated insulation voltage	250 V conforming to IEC 60947-1
[Ue] rated operational voltage	24...250 V AC 24...250 V DC
[Ith] conventional free air thermal current	5 A
Mechanical durability	100000 Cycles
Minimum switching current	2 MA
Minimum switching voltage	17 V
Protection type	GG fuse 5 A
Rated operational power in VA	400 VA at 230…240 V AC-12
Rated operational power in W	50 W at 24 V DC-12

Environment

Environmental characteristic	Normal environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 Cm
Package 1 Width	9 Cm
Package 1 Length	15.6 Cm
Package 1 Weight	150 G
Unit Type of Package 2	S02
Number of Units in Package 2	18
Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	3 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	50a98d63-e355-4cae-a24f-48edbc8c4dc5
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised