# Product data sheet
## Characteristics

# GV4P115N6
Motor circuit breaker, TeSys GV4, 3P, 115A, Icu 50kA, thermal magnetic, lugs terminals



## Main

| | |
|---|---|
| Range | TeSys Deca |
| Range of product | TeSys GV4 |
| Device short name | GV4P |
| Product name | TeSys GV4 |
| Product or component type | Motor circuit breaker |
| Device application | Motor protection |
| Trip unit technology | Electronic<br>Thermal-magnetic |

## Complementary

| | |
|---|---|
| Poles description | 3P |
| Utilisation category | Category A conforming to IEC 60947-2<br>AC-3 conforming to IEC 60947-4-1 |
| Operating position | Any position |
| Motor power kW | 37 KW at 400...415 V AC 50/60 Hz<br>45 KW at 400...415 V AC 50/60 Hz<br>55 KW at 400...415 V AC 50/60 Hz<br>45 KW at 500 V AC 50/60 Hz<br>55 KW at 500 V AC 50/60 Hz<br>75 KW at 500 V AC 50/60 Hz<br>75 KW at 660...690 V AC 50/60 Hz<br>90 KW at 660...690 V AC 50/60 Hz<br>110 KW at 660...690 V AC 50/60 Hz |
| Breaking capacity | 100 KA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>15 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>65 KA at 208Y/120 V AC 50/60 Hz conforming to UL 60947<br>65 KA at 240 V AC 50/60 Hz conforming to UL 60947<br>35 KA at 480Y/277 V AC 50/60 Hz conforming to UL 60947<br>8 KA Icu at 660...690 V AC 50/60 Hz conforming to IEC 60947-2<br>25 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>18 KA at 600Y/347 V AC 50/60 Hz conforming to UL 60947 |
| Control type | Rotary handle |
| [In] rated current | 115 A |
| Magnetic tripping current | 1955 A |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ui] rated insulation voltage | 800 V AC 50/60 Hz conforming to IEC 60947-2 |
| [Ith] conventional free air thermal current | 115 A conforming to IEC 60947-4-1 |
| [Uimp] rated impulse withstand voltage | 8 KV conforming to IEC 60947-2 |
| Power dissipation per pole | 4.6 W |
| Mechanical durability | 40000 Cycles |

| | |
|---|---|
| Electrical durability | 5000 Cycles for AC-3 at 415 V opening<br>5000 Cycles for AC-3 at 415 V closing |
| Maximum operating rate | 25 Cyc/H |
| Rated duty | Continuous conforming to IEC 60947-4-1 |
| Connection pitch | 27 Mm without spreaders<br>35 Mm with spreaders |
| Connections - terminals | Lugs-ring terminals |
| Tightening torque | 9 N.M for cable 16…95 mm²<br>5 N.M for cable 1.5…10 mm² |
| Mechanical robustness | Vibrations: +/- 1 mm 2...13.2 Hz conforming to IEC 60068-2-6<br>Vibrations: 0.7 gn 13.2...100 Hz conforming to IEC 60068-2-6<br>Shocks: 15 gn 11 ms conforming to IEC 60068-2-27 |
| Phase failure sensitivity | Yes conforming to IEC 60947-4-1 |
| Height | 155 Mm |
| Width | 81 Mm |
| Depth | 165 Mm |
| Net weight | 1.6 Kg |
| Colour | Grey (RAL 7016) |
| Suitability for isolation | Yes conforming to IEC 60947-1 |

## Environment

| | |
|---|---|
| Standards | CSA C22.2 No 60947-4-1<br>UL 60947-4-1<br>EN/IEC 60947-4-1<br>EN/IEC 60947-2 |
| Product certifications | IEC[RETURN]UL[RETURN]CSA[RETURN]CCC[RETURN]EAC[RETURN]ATEX[RETURN]EU-RO |
| Climatic withstand | Conforming to IACS E10 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Pollution degree | 3 |
| IP degree of protection | IP40 conforming to IEC 60529 |
| Ambient air temperature for storage | -50…85 °C |
| Fire resistance | 960 °C conforming to IEC 60695-2-11 |
| Operating altitude | 5000 m |
| Ambient air temperature for operation | -25…70 °C |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.600 Cm |
| Package 1 Width | 19.900 Cm |
| Package 1 Length | 22.200 Cm |
| Package 1 Weight | 1.554 Kg |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 3 |
| Package 2 Height | 30.000 Cm |
| Package 2 Width | 30.000 Cm |
| Package 2 Length | 40.000 Cm |
| Package 2 Weight | 6.000 Kg |
| Unit Type of Package 3 | PAL |
| Number of Units in Package 3 | 216 |
| Package 3 Height | 110.000 Cm |
| Package 3 Width | 80.000 Cm |
| Package 3 Length | 120.000 Cm |
| Package 3 Weight | 345.600 Kg |

## Offer Sustainability

| | |
|---|---|
| Recyclability potential, in % | 49 |
| Total lifecycle Carbon footprint | 91 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 11.980185990255322 |
| Carbon footprint of the manufacturing phase [A1 to A3] | 12 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 0.5066196486447603 |
| Carbon footprint of the distribution phase [A4] | 0.5 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 0.4514704866358834 |
| Carbon footprint of the installation phase [A5] | 0.5 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 74.322 |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 74 kg CO2 eq. |
| Mercury free | Yes |
| Sustainable packaging | Yes |
| Carbon footprint of the end-of-life phase [C1 to C4] | 4.082413374754788 |
| Carbon footprint of the end-of-life phase [C1 to C4] | 4 kg CO2 eq. |
| Environmental Disclosure | Product Environmental Profile |
| Total lifecycle Carbon footprint | 91 |
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| SCIP Number | 1b259a2c-3a3c-401a-acdd-f0837efd4018 |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| EU RoHS Directive | Compliant By Exemption |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, w |
| Halogen-free status | Halogen free plastic parts product |
| PVC free | Yes |
| End of life manual availability | End Of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection a |

## Contractual warranty

| | |
|---|---|
| Warranty (in months) | 18 |

Product Life Status : Commercialised