Product data sheet
Characteristics

GZ1E06
Motor circuit breaker,Easy TeSys Power,GZ1E,AC-3,3P,1..1.6A,thermal magnetic trip



Main

Range	Easy TeSys
Range of product	Easy TeSys Power
Product or component type	Circuit breaker
Device short name	GZ1E
Device application	Motor
Trip unit technology	Thermal-magnetic
Suitability for isolation	Yes conforming to IEC 60947-1 appendix 7.1.6
Colour	Grey (RAL 7011)

Complementary

Poles description	3P
Network type	AC
Utilisation category	AC-3
Network frequency	50/60 Hz conforming to IEC 60947-2
Mounting mode	By screws By clips
Mounting support	Rail
Mounting position	Any position
Motor power kW	0.37 KW at 400 V AC 50/60 Hz 0.55 KW at 440 V AC 50/60 Hz 0.75 KW at 500 V AC 50/60 Hz 1.1 KW at 690 V AC 50/60 Hz
Breaking capacity	Icu: >= 100 kA at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 Icu: >= 100 kA at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 Icu: >= 100 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 Icu: >= 100 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 Icu: >= 100 kA at 690 V AC 50/60 Hz conforming to IEC 60947-2
[Ics] rated service short-circuit breaking capacity	100 % at 230/240 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 400/415 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 440 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 % at 690 V AC 50/60 Hz conforming to IEC 60947-2
Control type	Push-button
Thermal protection adjustment range	1…1.6 A
Magnetic tripping current	22.5 A
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60947-2
Power dissipation	2.5 W (per pole)

Mechanical durability	100000 Cycles
Electrical durability	100000 Cycles for AC-3
Maximum operating rate	25 Cyc/H
Connections - terminals	Screw clamp terminals 2 1…6 mm² - cable stiffness: solid Screw clamp terminals 2 1.5…6 mm² - cable stiffness: flexible without cable end Screw clamp terminals 2 1…4 mm² - cable stiffness: flexible with cable end
Height	89 Mm
Width	44.5 Mm
Depth	78 Mm
Net weight	0.26 Kg

Environment

Standards	EN/IEC 60947-1 EN/IEC 60947-2 EN/IEC 60947-4-1 GB/T 14048.1 GB/T 14048.2 GB/T 14048.4 EN/IEC 60335-1:Clause 30.2 EN/IEC 60335-2-40:Annex JJ
Product certifications	CB Scheme[RETURN]CCC[RETURN]CE[RETURN]EAC
Protective treatment	TH
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20…60 °C
Ambient air temperature for storage	-40…80 °C
Fire resistance	960 °C conforming to IEC 60695-2-1
Operating altitude	2000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.800 Cm
Package 1 Width	8.400 Cm
Package 1 Length	9.000 Cm
Package 1 Weight	235.000 G
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15.000 Cm
Package 2 Width	30.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	5.987 Kg
Unit Type of Package 3	P06
Number of Units in Package 3	384
Package 3 Height	75.000 Cm
Package 3 Width	60.000 Cm
Package 3 Length	80.000 Cm
Package 3 Weight	104.300 Kg

Offer Sustainability

Recyclability potential, in %	57
Total lifecycle Carbon footprint	44 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	2.3653252415474544
Carbon footprint of the manufacturing phase [A1 to A3]	2 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5161838977394857
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.003881538122289672
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	40.39237713696235

Carbon footprint of the use phase [B2, B3, B4, B6]	40 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.6813379922935492
Carbon footprint of the end-of-life phase [C1 to C4]	0.7 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	44
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	25204872-3df4-48c8-9f77-906ce87e060b
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised