Product data sheet
Characteristics

HU365R
Safety switch, heavy duty, non fusible, 400A, 3 wire, 3 pole, 350hp, 600VAC/DC, NEMA 3R

Local Stock Code: On Stock

Price*: 3840.00 USD



Main

Product or component type	Single Throw Safety Switch
Series name	Heavy duty
Device application	Heavy application
Disconnector device type	Non-fusible disconnect
Device composition	None
Number of poles	3
[In] rated current	400 A
[Ue] rated operational voltage	600 V AC/DC
NEMA degree of protection	NEMA 3R galvannealed steel
Motor power hp	125 Hp at 240 V AC 50...60 Hz for 3 phases motors 250 Hp at 480 V AC 50...60 Hz for 3 phases motors 350 Hp at 600 V AC 50...60 Hz for 3 phases motors 50 Hp at 250 V DC 50 Hp at 600 V DC

Complementary

Device mounting	Surface
Electrical connection	Lugs
Wiring configuration	3-wire
AWG gauge	1/0 AWG...750 kcmil copper or aluminium
Tightening torque	62.1 N.M (1/0 AWG...750 kcmil)
Depth	257.30 Mm
Width	708.15 Mm
Height	1277.87 Mm
Net weight	84.8 Kg

Environment

Product certifications	UL listed file E154828

Ordering and shipping details

Category	US10DE100054
Discount Schedule	0DE1
GTIN	785901450481
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.0 Cm
Package 1 Width	73.0 Cm
Package 1 Length	130.0 Cm
Package 1 Weight	84.822 Kg
Unit Type of Package 2	PAL
Number of Units in Package 2	2
Package 2 Height	82.550 Cm
Package 2 Width	101.600 Cm
Package 2 Length	121.920 Cm
Package 2 Weight	169.643 Kg

Offer Sustainability

Recyclability potential, in %	90
Total lifecycle Carbon footprint	1 401 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	432.9412355197337
Carbon footprint of the manufacturing phase [A1 to A3]	433 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	214.72080951593014
Carbon footprint of the distribution phase [A4]	215 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.205059042943438
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	547.0206826529308
Carbon footprint of the use phase [B2, B3, B4, B6]	547 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	205.95222047374295
Carbon footprint of the end-of-life phase [C1 to C4]	206 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	1401
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	D0bd462c-e622-40b4-9939-dbd8b5850181
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is k
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and neve

Contractual warranty

Warranty (in months)	18

Product Life Status :	Commercialised