Product data sheet
Characteristics

ILS2T572PB1A0
integrated drive ILS with stepper motor - 24..48 V - Modbus TCP - 3.5 A



Main

Range of product	Lexium integrated drive
Product or component type	Motion integrated drive
Device short name	ILS
Motor type	3-phase stepper motor
Number of motor poles	6
Network number of phases	Single phase
[Us] rated supply voltage	48 V 24 V
Network type	DC
Communication interface	Modbus TCP, integrated
Length	115.9 Mm
Winding type	Medium speed of rotation and medium torque
Electrical connection	Printed circuit board connector
Holding brake	Without
Gear box type	Without
Nominal speed	1000 rpm at 48 V 500 rpm at 24 V
Nominal torque	0.9 N.M
Holding torque	0.9 N.M

Complementary

Transmission rate	10, 100 Mbits
Mounting support	Flange
Motor flange size	57 Mm
Number of motor stacks	2
Centring collar diameter	38.1 Mm
Centring collar depth	1.6 Mm
Number of mounting holes	4
Mounting holes diameter	5.2 Mm
Circle diameter of the mounting holes	66.6 Mm
Feedback type	Index pulse
Shaft end	Untapped
Second shaft	Without second shaft end
Shaft diameter	6.35 Mm
Shaft length	21 Mm
Supply voltage limits	18…55 V
Current consumption	3500 mA maximum continuous

Associated fuse rating	16 A
Commissioning interface	RS485 Modbus TCP (9.6, 19.2 and 38.4 kbauds)
Input/output type	4 signals (each be used as input or output)
Voltage state 0 guaranteed	-3...4.5 V
Voltage state 1 guaranteed	15...30 V
Discrete input current	10 MA at 24 V for safety input 2 MA at 24 V for 24 V signal interface
Discrete output voltage	23...25 V
Maximum switching current	100 MA per output 200 MA total
Protection type	Short circuit of the output voltage Safe torque off Overload of output voltage
Peak stall torque	0.9 N.M
Continuous stall torque	0.9 N.M
Speed feedback resolution	20000 points/turn
Accuracy error	+/- 6 arc min
Rotor inertia	0.22 Kg.Cm²
Maximum mechanical speed	3000 Rpm
Maximum radial force Fr	24 N
Maximum axial force Fa	100 N (tensile force) 8.4 N (force pressure)
Service life in hours	20000 H bearing
Marking	CE
Type of cooling	Natural convection
Net weight	1.6 Kg

Environment

Standards	IEC 50347 IEC 61800-3, Ed 2 IEC 50178 EN 61800-3:2001, second environment IEC 60072-1 IEC 61800-3 EN 61800-3 : 2001-02
Product certifications	UL[RETURN]cUL[RETURN]TÜV
Ambient air temperature for operation	40…55 °C (with power derating of 2 % per °C) 0…40 °C (without derating)
Permissible ambient air temperature around the device	105 °C power amplifier 110 °C motor
Ambient air temperature for storage	-25…70 °C
Operating altitude	<= 1000 m without derating
Relative humidity	15…85 % without condensation
Vibration resistance	20 m/s² (f= 10…500 Hz) 10 cycles conforming to IEC 60068-2-6
Shock resistance	150 m/s² 1000 shocks conforming to IEC 60068-2-29
IP degree of protection	IP41 shaft bushing: conforming to IEC 60034-5 IP54 total except shaft bushing: conforming to IEC 60034-5

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.000 Cm
Package 1 Width	17.000 Cm
Package 1 Length	24.000 Cm
Package 1 Weight	1.745 Kg
Unit Type of Package 2	S04
Number of Units in Package 2	8
Package 2 Height	30.000 Cm
Package 2 Width	40.000 Cm

Package 2 Length	60.000 Cm
Package 2 Weight	14.912 Kg

Offer Sustainability

Recyclability potential, in %	85
Total lifecycle Carbon footprint	341 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	20.76606825479816
Carbon footprint of the manufacturing phase [A1 to A3]	21 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2.577588532496949
Carbon footprint of the distribution phase [A4]	3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.9233601567524047
Carbon footprint of the installation phase [A5]	0.9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	314.74176693542233
Carbon footprint of the use phase [B2, B3, B4, B6]	315 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	No
Carbon footprint of the end-of-life phase [C1 to C4]	1.8549340277159516
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	341
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	F800009a-26ea-46d4-b613-164e8055f98f
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, w
PVC free	Yes
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection a

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised