Product data sheet
Characteristics

KDC1S
Cam switch operating head, Harmony K, 22mm, plastic, 45x45mm, key operated, 45 degreeet 90 degree, 601 A



Main

Range of product	Harmony Series K
Product or component type	Cam switch operating head
Component name	KDC
Product compatibility	Front mounting bodies 12 and 20 A by Ø 22 mm hole
Cam switch head type	With front plate 45 x 45 mm
Type of operator	Key 601A
Rotary handle padlocking	Without
Presentation of legend	Without
Switching angle	90 ° 45 °

Complementary

Mechanical durability	1000000 Cycles
CAD overall width	45 Mm
CAD overall height	45 Mm
CAD overall depth	69 Mm
Net weight	0.061 Kg

Environment

Protective treatment	TC
Ambient air temperature for operation	-25…55 °C
Ambient air temperature for storage	-40…70 °C
Shock resistance	30 gn conforming to IEC 68-2-27
Vibration resistance	5 gn conforming to IEC 68-2-6 (f = 10…150 Hz)
IP degree of protection	IP65 conforming to IEC 529 IP65 conforming to NF C 20-010

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.6 Cm
Package 1 Width	6.6 Cm
Package 1 Length	7.9 Cm
Package 1 Weight	68.0 G
Unit Type of Package 2	S02
Number of Units in Package 2	32

Package 2 Height	15 Cm
Package 2 Width	30 Cm
Package 2 Length	40 Cm
Package 2 Weight	2.631 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is know
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised