Product data sheet
Characteristics

KSA630ABG4
End feed unit, Canalis KSA630, aluminium, 500/630A, left mounting, without line protection, 3L+N+PE, white RAL9001



Main

Range of product	Canalis
Product name	KS
Device short name	KSA
Product compatibility	Canalis KSA busbar trunking 500…1000 A
Offer type	Classic
Product or component type	Feed unit
Material	Aluminium
[Ie] rated operational current	630 A
[Ue] rated operational voltage	230...690 V
Number of circuits	1
Busbar trunking polarity	3L + N + PE
Protection type	Without protection
Control type	Without
Colour	White (RAL 9001)

Complementary

Provided equipment	End cover
Mounting location	Left
Mounting mode	By screws
Mounting support	Busbar
Body material	Metal
Connections - terminals	Lug for 300 mm² rigid Lug for 300 mm² flexible
Width	753 Mm
Depth	288 Mm
Height	457 Mm
Net weight	23 Kg
Standards	IEC 61439-1 IEC 61439-6

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.4 Cm
Package 1 Width	50.0 Cm
Package 1 Length	76.1 Cm
Package 1 Weight	24.0 Kg
Unit Type of Package 2	P06
Number of Units in Package 2	2
Package 2 Height	79.0 Cm
Package 2 Width	80.0 Cm
Package 2 Length	60.0 Cm
Package 2 Weight	63.0 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Halogen free product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised