Product data sheet
Characteristics

KSB1000ZFKP1
Vertical pendant kit, Canalis KS 500A to 1000A



Main

Range of product	Canalis
Product name	KS
Product or component type	Bracket
Product compatibility	KS
Fixing device mounting	Under ceiling or I-Beam
Maximum load	80 Kg

Complementary

Accessory / separate part category	Fixing accessory
[Ie] rated operational current	1000.0 A
Width	135 Mm
Depth	428 Mm
Height	1 M
Net weight	2.8 Kg

Environment

Standards	IEC 61439-6 IEC 60439-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.100 Cm
Package 1 Width	13.500 Cm
Package 1 Length	39.400 Cm
Package 1 Weight	2.700 Kg
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Height	15.500 Cm
Package 2 Width	19.000 Cm
Package 2 Length	106.000 Cm
Package 2 Weight	11.018 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	64
Package 3 Height	75.000 Cm
Package 3 Width	80.000 Cm
Package 3 Length	120.000 Cm
Package 3 Weight	208.000 Kg

Offer Sustainability

REACh free of SVHC	Yes
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	No
Environmental Disclosure	Product Environmental Profile
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No, we have minimized the use of plastic in the packaging in compliance with regulations and cons
REACh Regulation	Free of Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant
Halogen-free status	Halogen free product
PVC free	Yes
Silicone-free	Yes
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised