Product data sheet
Characteristics

LA6DK10M
Mechanical latch block, TeSys Deca, 220...240V AC/DC



Main

Range	TeSys
Product or component type	Mechanical latch block
Product compatibility	LC1D40 3 phases + neutral AC LP1D40 3 phases + neutral DC LP1D65 3 phases + neutral DC LC1D65 3 phases + neutral AC
[Uc] control circuit voltage	220/240 V AC 50/60 Hz 220/240 V DC

Complementary

Mounting location	Front side
Tripping control	Electrical Manual
[Ui] rated insulation voltage	690 V conforming to IEC 60947-5-1
Power required in VA	25 for AC circuit
Power required in W	30 W for DC circuit
Mechanical durability	500000 Cycles
Maximum operating rate	1200 Cyc/H
On-load factor	10 %
Net weight	0.07 Kg

Environment

Product certifications	CSA[RETURN]UL
IP degree of protection	IP2X conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068
Ambient air temperature for operation	-25…55 °C
Ambient air temperature for storage	-40…80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.600 Cm
Package 1 Width	6.500 Cm
Package 1 Length	5.000 Cm
Package 1 Weight	98.000 G
Unit Type of Package 2	S01
Number of Units in Package 2	32
Package 2 Height	15.000 Cm

Package 2 Width	15.000 Cm
Package 2 Length	40.000 Cm
Package 2 Weight	3.356 Kg

Offer Sustainability

Recyclability potential, in %	49
Total lifecycle Carbon footprint	4 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0.5920425743346666
Carbon footprint of the manufacturing phase [A1 to A3]	0.6 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.020112505042928736
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.013852101990986205
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	3.1606
Carbon footprint of the use phase [B2, B3, B4, B6]	3 kg CO2 eq.
Mercury free	Yes
Sustainable packaging	Yes
Carbon footprint of the end-of-life phase [C1 to C4]	0.178431706032963
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Total lifecycle Carbon footprint	4
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	C7b64c73-e428-45b0-a9eb-af38721e12df
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
California proposition 65	WARNING: This product can expose you to chemicals including: Lead, which is known to the State
End of life manual availability	End Of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised