Product data sheet
Characteristics

LA9LB920
Current limiter, TeSys U / TeSys GV2, 32A/690V, activation 1kA, Iq 100kA@440V, DIN rail mounting



Main

Range	TeSys
Range of product	TeSys U TeSys GV2
Accessory / separate part category	Protection accessory
Product or component type	Current limiting module
Range compatibility	TeSys TeSys U TeSys TeSys GV2
Product compatibility	LUB LU2B GV2P GV2L GV2RT GV2ME
Function of module	Increasing the breaking capacity of a circuit breaker
Mounting location	35 mm DIN rail
[Ie] rated operational current	32 A
[Ith] conventional free air thermal current	63 A conforming to IEC 60947-1
Activation threshold	1000 A
Breaking capacity	<= 100 kA depending on protective device
[Ue] rated operational voltage	690 V AC 50/60 Hz
[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-1

Complementary

Connections - terminals	Screw clamp terminals 1 x 1.5…25 mm² rigid Screw clamp terminals 2 x 1.5…10 mm² rigid Screw clamp terminals 1 x 1.5…25 mm² flexible without cable end Screw clamp terminals 2 x 1.5…10 mm² flexible without cable end Screw clamp terminals 1 x 1.5…16 mm² flexible with cable end Screw clamp terminals 2 x 1.5…4 mm² flexible with cable end
Tightening torque	2.2 N.M
Net weight	0.32 Kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 Cm
Package 1 Width	8.5 Cm
Package 1 Length	15.7 Cm
Package 1 Weight	346.9 G

Unit Type of Package 2	S02
Number of Units in Package 2	12
Package 2 Height	15.0 Cm
Package 2 Width	30.0 Cm
Package 2 Length	40.0 Cm
Package 2 Weight	4.494 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
SCIP Number	04104e70-ba29-493c-b2cc-b5837d1f879b
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
POP Directive	No POPs
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised