Product data sheet
Characteristics

LA9ZX01495
Busbar support, Linergy BZ, Support 3P for 60 Interaxis Busbar IEC



Main

Range	Linergy
Product or component type	Busbar support
Device short name	LA9Z
Product name	BZ
Quantity per set	Set of 10

Complementary

Range compatibility	TeSys
[Ui] rated insulation voltage	690 V conforming to IEC 60947-1 690 V conforming to NF C 20-040
Permissible current	200 A - busbar cross section: 12 x 5 mm 250 A - busbar cross section: 15 x 5 mm 320 A - busbar cross section: 20 x 5 mm 400 A - busbar cross section: 25 x 5 mm 450 A - busbar cross section: 30 x 5 mm 360 A - busbar cross section: 12 x 10 mm 520 A - busbar cross section: 20 x 10 mm 630 A - busbar cross section: 30 x 10 mm
Distance between supports	570 Mm
Busbar pitch	60 Mm
Poles description	3P
Colour	Grey

Environment

IP degree of protection	IP20 with protective cover
Temperature resistance	125 °C
Standards	UL 508 IEC 61439-2
Product certifications	IEC

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 Cm
Package 1 Width	6.300 Cm
Package 1 Length	19.400 Cm
Package 1 Weight	143.000 G
Unit Type of Package 2	BB1
Number of Units in Package 2	10

Package 2 Height	14.000 Cm
Package 2 Width	11.400 Cm
Package 2 Length	20.800 Cm
Package 2 Weight	1.449 Kg
Unit Type of Package 3	S03
Number of Units in Package 3	50
Package 3 Height	30 Cm
Package 3 Width	30 Cm
Package 3 Length	40 Cm
Package 3 Weight	7.980 Kg

Offer Sustainability

Mercury free	Yes
Sustainable packaging	Yes
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
EU RoHS Directive	Compliant By Exemption
Halogen-free status	Halogen free plastic parts product
PVC free	Yes
Silicone-free	Yes
Take-back	No

Contractual warranty

Warranty (in months)	18

Product Life Status : Commercialised